


PERFORMANCE DATA SHEET

Model: PureAdvantage Ultra-U Using Replacement Cartridge EWF02

| APPLICATION GUIDELINES / CONDITIONS OF USE | |
|---|--------------------------------------|
| Water Supply | Potable Water |
| Water Temp. | Max. 100°F (38°C), Min. 33°F (0.6°C) |
| Water Pressure | 30 - 100 psi (206.8 - 689.5 kPa) |
| Service Flow | 0.65 gpm maximum (2.46 lpm) |
| <ul style="list-style-type: none"> It is essential that the manufacturer's recommended installation, maintenance and filter replacement requirements be carried out for the product to perform as advertised. See Installation Manual for Warranty information. While testing was performed under standard laboratory conditions, actual performance may vary. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standard 42, Standard 53 and Standard 401. The compounds certified under NSF 401 have been deemed as "emerging compounds/incidental contaminants. Emerging compounds/incidental contaminants are those compounds that have been detected in drinking water supplies at trace levels. While occurring at only trace levels, these compounds can affect the public acceptance/perception of drinking water quality. | |

| REPLACEMENT CARTRIDGE INFORMATION | |
|--|--------------------------|
| Replacement Element: EWF02. For estimated cost of replacement elements please call 1-800-599-7569 or visit us on the web at http://www.Electrolux-store.com | |
| PERFORMANCE DATA | |
| MODEL: PureAdvantage Ultra-U. Use the replacement cartridge EWF02. | |
|  System tested and certified by NSF International against NSF/ANSI Standard 42, Standard 53, and Standard 401 for the reduction of substances listed below. | |
| SYSTEM SPECIFICATIONS | |
| Capacity | 200 gallons (757 liters) |

WARNING

To reduce the risk associated with ingestion of contaminants:

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before and after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

EPA Establishment Number 10350-MN-005

CAUTION

To reduce the risk associated with property damage due to water leakage or flooding:

Read and follow all Instructions before installation and use of this system.

To reduce the risk of water leakage or flooding, and ensure optimal filter performance:

- Change the disposable filter cartridge every six months or sooner if you observe a noticeable reduction in water flow rate.
- Failure to replace the disposable filter cartridge at recommended intervals may lead to reduced filter performance and cracks in the filter housing, causing water leakage or flooding.

| Contaminant Reduction | Average Influent | NSF/ANSI Specified Challenge Concentration | Avg % Reduction | Average Product Water Concentration | Max Permissible Product Water Concentration | NSF Reduction Requirements | NSF Test Report |
|--|------------------|---|-----------------|-------------------------------------|---|----------------------------|-----------------|
| Chlorine Taste and Odor | 2.0 mg/L | 2.0 mg/L ± 10% | 97.5% | 0.05 mg/L | N/A | ≥ 50% | J-00124057 |
| Nominal Particulate Class I, ≥0.5 to < 1.0 µm | 9,600,000 pts/mL | At least 10,000 particles/mL | 99.9% | 23,000 pts/ml | N/A | ≥85% | J-00124061 |
| Asbestos | 71 MFL | 107 to 108 MFL; fibers greater than 10 µm in length | >99% | < 1MLF | N/A | ≥99% | J-00124503 |
| Atrazine | 0.009 mg/L | 0.009 mg/L ± 10% | 94.3% | 0.0005 mg/L | 0.003 mg/L | N/A | J-00124514 |
| Benzene | 0.014 mg/L | 0.015 mg/L ± 10% | 96.3% | 0.0005 mg/L | 0.005 mg/L | N/A | J-00124500 |
| Carbofuran | 0.08 mg/L | 0.08 mg/L ± 10% | 94% | 0.002 mg/L | 0.04 mg/L | N/A | J-00124513 |
| Cyst* | 92,500 cysts/L | Minimum 50,000 cysts/L | 99.99% | <1 cyst/L | N/A | ≥99.95% | J-00124062 |
| Endrin | 0.006 mg/L | 0.006 mg/L ± 10% | 96.8% | 0.0002 mg/L | 0.002 mg/L | N/A | J-00124527 |
| Lead pH @6.5 | 0.147 mg/L | 0.15 mg/L ± 10% | >99.3% | 0.001 mg/L | 0.010 mg/L | N/A | J-00124063 |
| Lead pH @8.5 | 0.150 mg/L | 0.15 mg/L ± 10% | >99.3% | 0.001 mg/L | 0.010 mg/L | N/A | J-00124064 |
| Lindane | 0.002 mg/L | 0.002 mg/L ± 10% | 99.1% | 0.0002 mg/L | 0.0002 mg/L | N/A | J-00124520 |
| Mercury @ pH 6.5 | 0.006 mg/L | 0.006 mg/L ± 10% | 96.6% | 0.0002 mg/L | 0.002 mg/L | N/A | J-00124498 |
| Mercury @ pH 8.5 | 0.006 mg/L | 0.006 mg/L ± 10% | 93% | 0.0003 mg/L | 0.002 mg/L | N/A | J-00124499 |
| O-Dichlorobenzene | 1.9 mg/L | 1.8 mg/L ±10% | 99.9% | 0.0005 mg/L | 0.6 mg/L | N/A | J-00124528 |
| P-Dichlorobenzene | 0.250 mg/L | 0.225 mg/L ± 10% | 99.8% | 0.0005 mg/L | 0.075 mg/L | N/A | J-00124502 |
| Tetrachloroethylene | 0.014 mg/L | 0.015 mg/L ± 10% | 96.4% | 0.0005 mg/L | 0.005 mg/L | N/A | J-00124525 |
| Toxaphene | 0.017 mg/L | 0.015 mg/L ± 10% | 94% | 0.001 mg/L | 0.003 mg/L | N/A | J-00124501 |
| 2,4-D | 0.210 mg/L | 0.210 mg/L ± 10% | 98.9% | 0.002 mg/L | 0.07 mg/L | N/A | J-00124518 |
| Atenolol | 1350 ng/L | 200 ng/L ± 20% | 99.6% | 5.0 ng/L | 30 ng/L | N/A | J-00124521 |
| Bisphenol A | 2,111 ng/L | 2000 ng/L ± 20% | >99.1% | 20 ng/L | 300 ng/L | N/A | J-00135911 |
| Estrone | 152 ng/L | 140 ng/L ± 20% | >96.7% | 5.0 ng/L | 20 ng/L | N/A | J-00135911 |
| Naproxen | 140 ng/L | 140 ng/L ± 20% | >96.4% | 5 ng/L | 20 ng/L | N/A | J-00135911 |
| Nonylphenol | 1500 ng/L | 1400 ng/L ± 20% | >96.7% | 50 ng/L | 200 ng/L | N/A | J-00135911 |
| Phenytoin | 221 ng/L | 200 ng/L ± 20% | >95.5% | 10 ng/L | 30 ng/L | N/A | J-00135911 |
| Trimethoprim | 675 ng/L | 140 ng/L ± 20% | 99.3% | 2.0 ng/L | 20 ng/L | N/A | J-00124521 |
| **The following Pharmaceutical reduction claims have not been certified by NSF International. Claims tested and verified by independent laboratory: | | | | | | | |
| Fluoxetine** | 845 ng/l | N/A | 99.4% | 5.0 ng/L | N/A | N/A | J-00124521 |
| Ibuprofen** | 1012 ng/L | N/A | 85.2% | 150 ng/L | N/A | N/A | J-00124523 |
| Progesterone** | 945 ng/L | N/A | 99.4% | 5.5 ng/L | N/A | N/A | J-00124522 |

Contaminant reduction determined by NSF testing.

* Based on the use of Cryptosporidium parvum oocysts



10200 David Taylor Drive, Charlotte, NC 28262
 Electrolux 2015 ELECTROLUX HOME PRODUCTS, INC. 1-800-599-7569
 NSF is a trademark of NSF International.

ELECTROLUX P/N: A02686301
 3M P/N: 34-8716-1082-9

PERFORMANCE DATA SHEET

Model: PureAdvantage Ultra-M Using Replacement Cartridge EWF02


| APPLICATION GUIDELINES / CONDITIONS OF USE | |
|--|--------------------------------------|
| Water Supply | Potable Water |
| Water Temp. | Max. 100°F (38°C), Min. 33°F (0.6°C) |
| Water Pressure | 30 - 100 psi (206.8 - 689.5 kPa) |
| Service Flow | 0.65 gpm maximum (2.46 lpm) |
| <ul style="list-style-type: none"> It is essential that the manufacturer's recommended installation, maintenance and filter replacement requirements be carried out for the product to perform as advertised. See Installation Manual for Warranty information. While testing was performed under standard laboratory conditions, actual performance may vary. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standard 42, Standard 53 and Standard 401. The compounds certified under NSF 401 have been deemed as "emerging compounds/incidental contaminants". Emerging compounds/incidental contaminants are those compounds that have been detected in drinking water supplies at trace levels. While occurring at only trace levels, these compounds can affect the public acceptance/perception of drinking water quality. | |

WARNING

To reduce the risk associated with ingestion of contaminants:

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before and after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

EPA Establishment Number 10350-MN-005

| REPLACEMENT CARTRIDGE INFORMATION | |
|---|--|
| Replacement Element: EWF02. For estimated cost of replacement elements please call 1-800-599-7569 or visit us on the web at http://www.Electrolux-store.com | |
| PERFORMANCE DATA | |
| MODEL: PureAdvantage Ultra-M. Use the replacement cartridge EWF02. | |
|  | System tested and certified by NSF International against NSF/ANSI Standard 42, Standard 53, and Standard 401 for the reduction of substances listed below. |
| SYSTEM SPECIFICATIONS | |
| Capacity | 125 gallons (473 liters) |

CAUTION

To reduce the risk associated with property damage due to water leakage or flooding:

Read and follow all Instructions before installation and use of this system.

To reduce the risk of water leakage or flooding, and ensure optimal filter performance:

- Change the disposable filter cartridge every six months or sooner if you observe a noticeable reduction in water flow rate.
- Failure to replace the disposable filter cartridge at recommended intervals may lead to reduced filter performance and cracks in the filter housing, causing water leakage or flooding.

| Contaminant Reduction | Average Influent | NSF/ANSI Specified Challenge Concentration | Avg % Reduction | Average Product Water Concentration | Max Permissible Product Water Concentration | NSF Reduction Requirements | NSF Test Report |
|--|------------------|---|-----------------|-------------------------------------|---|----------------------------|-----------------|
| Chlorine Taste and Odor | 2.0 mg/L | 2.0 mg/L ± 10% | 97.5% | 0.05 mg/L | N/A | ≥ 50% | J-00124057 |
| Nominal Particulate Class I, ≥0.5 to < 1.0 µm | 9,600,000 pts/mL | At least 10,000 particles/mL | 99.9% | 23,000 pts/ml | N/A | ≥85% | J-00124061 |
| Asbestos | 71 MFL | 107 to 108 MFL; fibers greater than 10 µm in length | >99% | < 1MLF | N/A | ≥99% | J-00124503 |
| Atrazine | 0.009 mg/L | 0.009 mg/L ± 10% | 94.3% | 0.0005 mg/L | 0.003 mg/L | N/A | J-00124514 |
| Benzene | 0.014 mg/L | 0.015 mg/L ± 10% | 96.3% | 0.0005 mg/L | 0.005 mg/L | N/A | J-00124500 |
| Carbofuran | 0.08 mg/L | 0.08 mg/L ± 10% | 94% | 0.002 mg/L | 0.04 mg/L | N/A | J-00124513 |
| Cyst* | 92,500 cysts/L | Minimum 50,000 cysts/L | 99.99% | <1 cyst/L | N/A | ≥99.95% | J-00124062 |
| Endrin | 0.006 mg/L | 0.006 mg/L ± 10% | 96.8% | 0.0002 mg/L | 0.002 mg/L | N/A | J-00124527 |
| Lead pH @6.5 | 0.147 mg/L | 0.15 mg/L ± 10% | >99.3% | 0.001 mg/L | 0.010 mg/L | N/A | J-00124063 |
| Lead pH @8.5 | 0.150 mg/L | 0.15 mg/L ± 10% | >99.3% | 0.001 mg/L | 0.010 mg/L | N/A | J-00124064 |
| Lindane | 0.002 mg/L | 0.002 mg/L ± 10% | 99.1% | 0.0002 mg/L | 0.0002 mg/L | N/A | J-00124520 |
| Mercury @ pH 6.5 | 0.006 mg/L | 0.006 mg/L ± 10% | 96.6% | 0.0002 mg/L | 0.002 mg/L | N/A | J-00124498 |
| Mercury @ pH 8.5 | 0.006 mg/L | 0.006 mg/L ± 10% | 93% | 0.0003 mg/L | 0.002 mg/L | N/A | J-00124499 |
| O-Dichlorobenzene | 1.9 mg/L | 1.8 mg/L ±10% | 99.9% | 0.0005 mg/L | 0.6 mg/L | N/A | J-00124528 |
| P-Dichlorobenzene | 0.250 mg/L | 0.225 mg/L ± 10% | 99.8% | 0.0005 mg/L | 0.075 mg/L | N/A | J-00124502 |
| Tetrachloroethylene | 0.014 mg/L | 0.015 mg/L ± 10% | 96.4% | 0.0005 mg/L | 0.005 mg/L | N/A | J-00124525 |
| Toxaphene | 0.017 mg/L | 0.015 mg/L ± 10% | 94% | 0.001 mg/L | 0.003 mg/L | N/A | J-00124501 |
| VOC | 0.290 mg/L | 0.300 mg/L ± 10% | 99% | 0.001 mg/L | N/A | ≥95% | J-00127640 |
| 2,4-D | 0.210 mg/L | 0.210 mg/L ± 10% | 98.9% | 0.002 mg/L | 0.07 mg/L | N/A | J-00124518 |
| Atenolol | 1350 ng/L | 200 ng/L ± 20% | 99.6% | 5.0 ng/L | 30 ng/L | N/A | J-00124521 |
| Bisphenol A | 2,111 ng/L | 2000 ng/L ± 20% | >99.1% | 20 ng/L | 300 ng/L | N/A | J-00135911 |
| Estrone | 152 ng/L | 140 ng/L ± 20% | >96.7% | 5.0 ng/L | 20 ng/L | N/A | J-00135911 |
| Naproxen | 140 ng/L | 140 ng/L ± 20% | >96.4% | 5 ng/L | 20 ng/L | N/A | J-00135911 |
| Nonylphenol | 1500 ng/L | 1400 ng/L ± 20% | >96.7% | 50 ng/L | 200 ng/L | N/A | J-00135911 |
| Phenytoin | 221 ng/L | 200 ng/L ± 20% | >95.5% | 10 ng/L | 30 ng/L | N/A | J-00135911 |
| Trimethoprim | 675 ng/L | 140 ng/L ± 20% | 99.3% | 2.0 ng/L | 20 ng/L | N/A | J-00124521 |
| **The following Pharmaceutical reduction claims have not been certified by NSF International. Claims tested and verified by independent laboratory: | | | | | | | |
| Fluoxetine** | 845 ng/l | N/A | 99.4% | 5.0 ng/L | N/A | N/A | J-00124521 |
| Ibuprofen** | 1012 ng/L | N/A | 85.2% | 150 ng/L | N/A | N/A | J-00124523 |
| Progesterone** | 945 ng/L | N/A | 99.4% | 5.5 ng/L | N/A | N/A | J-00124522 |

Contaminant reduction determined by NSF testing.

* Based on the use of Cryptosporidium parvum oocysts



Electrolux

10200 David Taylor Drive, Charlotte, NC 28262, 2015 ELECTROLUX HOME PRODUCTS, INC. 1-800-599-7569
NSF is a trademark of NSF International.